

MATERIAL SAFETY DATA SHEET		SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the hazardous effects of normal products of combustion.	Floors may be slippery, use care to avoid falls. Flush final traces with water. Keep spills and cleaning run-off materials out of municipal sewers or open bodies of water.
MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (800) 424-9300 ADDRESS: 8689 W. Sahara Ave., Suite 160 Las Vegas, NV 89117-5871 Revised: January 2006 Information. Phone: (888) 277-8834		SECTION V - REACTIVITY DATA	WASTE DISPOSAL METHOD: Disposal should be in accordance with Federal, state and local regulations for water-based coatings. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Incinerate the solids and contaminated diking material at a permitted facility, according to Federal, State and local regulations.
SECTION I - PRODUCT ID.		STABILITY: Stable. CONDITIONS TO AVOID: <i>Keep from freezing.</i> INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable. HAZARDOUS POLYMERIZATION: Will not occur HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Will not occur.	PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: <i>KEEP FROM FREEZING.</i>
PRODUCT NUMBER: SE-120 PRODUCT NAME: Protective-Skin PRODUCT CLASS: Acrylic Elastomeric Coating.		SECTION VI - HEALTH HAZARD DATA	SECTION VIII - CONTROL MEASURES.
SECTION II - HAZARDOUS INGREDIENTS		EFFECTS OF OVEREXPOSURE: INHALATION of excessive vapor/mist can cause headache, nausea and irritation of the nose, throat and lungs. EYE CONTACT: slightly irritating to eyes. SKIN EXPOSURE: irritating to skin upon Prolonged or repeated contact.	VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS.
None known at a hazardous level. HMIS Hazard Rating = 0 0 0 J This product contains no heavy metals or fibers.		EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject.	RESPIRATORY PROTECTION: Wear respirator (MSHA or NIOSH APPROVED or the equivalent) ORGANIC VAPOR/PARTICULATE RESPIRATOR. IN CASE OF POOR VENTILATION (or exposure to spray mist), USE NIOSH APPROVED ORGANIC VAPOR MASK.
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS		OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.	PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT.
APPEARANCE: Milky white liquid BOILING POINT: 100°C (212°F) SPECIFIC GRAVITY: 1.3 – 1.5 (H ₂ O = 1.0) VAPOR PRESSURE: (mm Hg @ 20°C) = 18 VAPOR DENSITY: lighter than 1.0 EVAPORATIVE RATE: less than 1.0 PERCENT VOLATILE (by volume): 40%		SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE.	EYE PROTECTION: CHEMICAL SPLASH GOGGLES (ANSI 2-87.1) or EQUIVALENT.
SECTION IV - FIRE & EXPLOSION HAZARD DATA		STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer to containers for recovery or disposal.	OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Showers and cleaning of clothes are recommended. Use approved clothing when working around ACM or lead-based paints.
FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED. FLASH POINT - N/A LEL - N/A EXTINGUISHING MEDIA: N/A UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F. Polymer film can burn.			SECTION IX - REGULATORY INFO.
SE-120-msds-01-2006			DOT PROPER SHIPPING NAME: Not Regulated. Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.